



# Suppress

SI0003

## INDUSTRIAL

### GUARANTEED ANALYSIS

Magnesium (Mg)	9.2% w/v
Chlorine (Cl)	26.9% w/v
Specific Gravity @ 20°C	1.28 kg/L
pH	6.0 to 7.0

**WARNING:**  
**KEEP OUT OF REACH OF CHILDREN**

20 L



## GENERAL USE INFORMATION

Suppress is designed for application to road and clay surfaces. This product is applied as a liquid to control dust and erosion on unimproved (dirt or gravel) roads and dusty job sites such as quarries. Due to its hygroscopy it absorbs moisture from the air, limiting the number of smaller particles (silts and clays) which become airborne. This product expedites the compaction process by slowing the rate of evaporation of moisture from the road and as an aid in the overall retention of moisture, hence continuing the compaction process during the service life of the treated area.

### Typical Application Rates:

1.8 L per m<sup>2</sup> or 1,000 L per 500 m<sup>2</sup>.

Traffic can immediately use the area following application although it should be initially be slowed to reduce splashing and tracking. Care should be taken to eliminate spillage on sealed roads due to possible slipperiness.

Suppress should not be applied to plant root systems due to its strong hygroscopic properties that can interfere with the plants uptake of water.

## PRODUCT INFORMATION

### PRODUCT STORAGE

Keep material in a shaded, cool, dry, well ventilated area. Store product in suitable containers made from material such as stainless steel, high density polyethylene and fibreglass. This product can be corrosive to material such as brass, copper, zinc or alloys of these metals. Clean equipment after application of Suppress thoroughly with clean fresh water. This product is recommended for use within 12 months from dispatch date.

### WARNING & SAFETY INFORMATION

**WARNING:** Do not swallow. Fumes from this product may act as an irritant, use with adequate ventilation. Avoid inhalation and contact with the eyes and skin. Wear rubber gloves and appropriate eye protection when handling the product. See the product MSDS for further information - [www.sltec.com.au](http://www.sltec.com.au)

### IMPURITIES

Cadmium (Cd) 1.5 mg/kg

Batch No. or Tank Number & Date:

Dispatch Date:

PO Box 43 / 2055 Finlay Road  
TONGALA VICTORIA 3621  
P: (03) 5859 1323 F: 03 5859 1363  
E: [enquiries@sltec.com.au](mailto:enquiries@sltec.com.au)  
ABN: 63 234 073 378 ACN: 113 670 269  
[www.sltec.com.au](http://www.sltec.com.au)